PAPER DETAILS

TITLE: Utilizing an integrated AHP-COPRAS approach for battery selection in electric vehicles

AUTHORS: Asli Abdulvahitoglu, Gözde Ekmekçi Güçlüten

PAGES: 121-132

ORIGINAL PDF URL: https://dergipark.org.tr/tr/download/article-file/3329486



e-ISSN: 2146 - 9067

International Journal of Automotive Engineering and Technologies

journal homepage:

https://dergipark.org.tr/en/pub/ijaet

Original Research Article

ARTICLE INFO

Utilizing an integrated AHP-COPRAS approach for battery selection in electric vehicles

ABSTRACT





Aslı Abdulvahitoğlu^{1,*}, Gözde Ekmekçi Güçlüten²

1,*2 Adana Alparslan Türkeş Science and Technology University, Engineering Faculty, Mechanical Engineering Department, Adana,

Türkiye.

Orcid Numbers Internal combustion engine vehicles provide better performance and 1.0000-0002-3603-6748 longer-range using fossil fuels such as gasoline and diesel. However, 2.0000-0003-0392-1369 fossil fuels are non-renewable and cause environmental pollution, alternative fuels such as blends of ethanol and biodiesel, hydrogen etc Doi: 10.18245/ijaet.1342516 have been sought for these vehicles. On the other hand, some researchers prefer to design alternative vehicles such as hybrid and electrical vehicles, instead of changing the fuel type. Among the studied topics for * Corresponding author alternative vehicles, the battery is one of the most important components, aabdulvahitoglu@atu.edu.tr especially in electrical vehicles. Batteries are diversified with different criteria such as battery life, nominal voltage, energy density, volumetric energy density, specific power, operating temperature, and production Received: Feb 13, 2023 cost. In this study, the expert perspective was utilized when selecting the Accepted: Oct 04, 2023 battery type to be employed for the energy source through utilizing the Integrated Analytical Hierarchy Process (AHP) - Complex Proportional Published: 31 Dec 2023 Assessment (COPRAS), a multi-criteria decision-making approach. Various batteries such as Lead-acid (Pb-acid), Nickel-cadmium (Ni-Cd), Ni-MH, Sodium Nickel Chloride (Zero Emission Battery Research Activity-ZEBRA), Lithium -Ion (Li-Ion) Battery were evaluated in terms of different criterion. Among the alternatives the Li-ion battery type is Published by Editorial Board Members of chosen as the best option and the Ni-Cd battery is the least chosen alternative. © This article is distributed by Turk Journal Park System under the CC 4.0 terms and Keywords: Battery Selection, Electric Vehicle, AHP, COPRAS, Multi-Criteria Decision-Making

1. Introduction

IJAET

conditions.

Traditional automobiles, also known as internal combustion engine vehicles (ICEVs), are often because of their efficiency used and accessibility to fuel. However, they run on fossil fuels and emit dangerous pollutants including carbon monoxide, nitrogen oxides and unburn hydrocarbons. Particularly, the transportation industry is the source of these dangerous exhaust gases. It has been demonstrated that these gases substantially affect the health of living beings, particularly humans [1]. Concerns regarding climate change have driven the need for eco-conscious substitutes for regular internal combustion engine (ICE) cars, aiming to cut down on greenhouse gas and carbon discharges. Electric vehicles (EVs) are gaining traction as an environmentally mindful, reduced-carbon, and enduring substitute for internal combustion engines (ICEs) [2]. Since their historical growth began in the 19th century, electric vehicles (EVs) have gained popularity, especially in light of the rise in greenhouse gases and air pollution brought on by internal combustion engines. The quantity of EVs in operation has surged significantly over the past ten years, rising from 17,000 in 2010 to over 15 million by 2021 [3]. According to Turkish Standard Instute, there are 14,706,162 registered vehicles in Türkiye. Approximately 98.5% of the registered vehicles are fossil-fueled (27.8% gasoline, 36.4% diesel, 34.3% LPG), 1.2% hybrid, and 0.2% electrical vehicles [4].

Studies on various EV kinds are becoming more prevalent every day. Three categories best describe the types of EVs now in use. The first item that typically springs to mind is EVs, also known as All Electric Vehicles, which derive all of their energy from a battery pack. Recently, as battery technology has advanced, interest in allelectric vehicles has grown. However, hybrid electric vehicles—which combine an internal combustion engine with an electric motor for propulsion—are among the most popular types of EVs today. The literature refers to another form of EV as fuel cell electric vehicles that use hydrogen energy [5].

Compared to cars powered by internal combustion engines, electric vehicles use quite different technology. These automobiles utilize electric motors that utilise electric energy [6]. Parts used in energy storage and conversion include batteries, fuel cells, and supercapacitors, which are all members of the energy converter family. To meet the varied energy needs of different devices and systems, all three are necessary. However, they are unable to handle all applications on their own [7].

Batteries are the essential power source for electric vehicles, utilizing chemical reactions to supply energy for vehicle functioning. This approach obviates the necessity for fossil fuels, provided the electricity fueling EVs originates from sustainable sources. During discharge, batteries transform chemical energy into electrical energy, and during charging, they reverse this process, converting electrical energy back into chemical energy. Batteries serve as reliable storage units for energy, offering diverse power and capacity options. Achieved by connecting battery cells in series or parallel, this flexibility enables their application in various contexts.

The batteries in EVs are their most costly component. EV battery costs were on average \$750/kWh in 2010, \$500/kWh in 2012, and \$380/kWh in 2014. Since then, the cost has dropped significantly. It is predicted that the unit cost of EVs would reduce as a result of this anticipated decline, increasing consumer buying power [8]. Battery technology is the most important piece of technology for the creation of electric cars. The battery types that will be employed in this study will be briefly described before delving into the specifics of the battery chemistry of electric cars [9].

(Pb-Acid) Battery: Lead-acid Lead-acid batteries are the most traditional and wellknown kind of rechargeable batteries. This battery technology is so popular across the world for several reasons. The technology that underpins lead-acid batteries is straightforward, affordable to produce, widely used, and simple to build. The comparatively compact batteries are strong and dependable, and they require almost little maintenance. They also fit easily inside the engine compartment. The relatively short cycle life and working life of the battery, however, are the limiting considerations for these batteries. Lead-acid batteries typically last 5 to 15 years [10] or 1200 to 1800 chargedischarge cycles.

Nickel-cadmium (Ni-Cd) Battery: Nickelcadmium batteries have a long lifespan and may be completely depleted without suffering any harm. It discharges current at a rapid rate. Higher specificity and gravitational energy density than lead-acid batteries. Both its power and cycle life are longer. The expensive nature of this battery is one of the factors limiting its utilisation. The high expense of recycling the material is the major cause of this. Cadmium is a heavy metal that is exceedingly hazardous and may pollute the environment if improperly disposed of [11].

Ni-MH Battery: The most popular nickel-based battery is the Ni-MH, which entered the market in 1991. Compared to lead-acid and nickelcadmium batteries, it has a higher weight energy density and specific power. But they are also more expensive than lead-acid batteries due to the greater price of nickel and hydride-storing metals. They are free of poisonous substances. Ni-MH batteries are not promising batteries because of the high nickel content and high nickel costs. Ni-MH batteries are not promising batteries because of the high nickel content and high nickel costs [12].

ZEBRA Battery: Zebra batteries are another name for Sodium Nickel Chloride (NaNiCl) batteries. The project "Zero Emission Battery Research Activity" gave rise to the moniker Zebra. Lead acid and nickel-based batteries have lower energy density and nominal voltage values. This battery's drawbacks are low specific power, self-discharge issue, and temperature control [8].

Li-Ion Battery: When compared to other battery types like Pb-acid and Ni-MH, Li-ion batteries stand out as one of the most innovative energy storage options due to their properties like high energy and power densities and extended shelf lives. There is a lot of energy that can be held per unit of weight and volume. However, the lifespan of a lithium-ion battery is temperaturedependent; at higher temperatures, ageing occurs considerably more quickly, and deep discharges significantly shorten the cycle life. Li-ion batteries are particularly vulnerable to overcharging and deep discharge, which can harm them, decrease their lifespans, and even put them in risky circumstances [13].

In multi-criteria decision-making, first, the problem is determined, then the problem is structured and the result is reached by using the model. The processes they follow are normalization of data, weighting of criteria and ranking of alternatives. There are many weighting methods in the literature such as AHP, SWARA, CRITIC, ENTROPY, and DEMATEL decision-making methods in the literature. Such as AHP, ANP, TOPSIS, ARAS, WASPAS, CODAS, COPRAS, MABAC, MAIRCA [14]. MCDM is used in almost every area where the decision is needed such as Chemistry [15], Earth and Planetary Sciences [16], Economics, Econometrics and Finance [17], Material Science [18], Energy [19, 20, 21, 22, 23, 24, 25], Agricultural and Biological Science [26] Environmental Science [27,28], Decision Science [29,30], Business, Management Accounting[31]. and Engineering[32,33], Computer Science [34,35]. Loganathan et al. developed a multi-criteria decision-making technique-based methodology, with categories depending on cathode/anode material for the selection of Li-ion batteries. The technique helps original equipment manufacturers of electric vehicles choose the optimum battery and optimize the price and efficiency of electric vehicles. The Lithium-Titanate (Li₄Ti₅O₁₂) battery was shown to be the best all-around battery appropriate for electric vehicle applications as a consequence of the presented technique [36].

Sonar and Kulkarni sought to present the best alternative in current electric vehicles by combining the analytical hierarchy process (AHP) and the multi-attribute boundary approach area comparison (MABAC) method as a multi-criteria decision-making tool (MCDM) for the selection and ranking of the best alternative. According to the AHP weighting, the driving range received more attention from the experts. The Hyundai Kona is picked as the top option based on the performance selection criteria used in the MABAC approach since it has the greatest performance score of all the alternatives considered. For clients looking for inexpensive cars where price is a major concern, Tata Tigor has done well [37].

Chakraborty and Saha used a multi-criteria group decision making (MCGDM) approach to determine the optimal recycling strategy for Lithium-Ion Batteries in a Fermatean fuzzy environment (FFE). Under FFE, a new entropy measure (EM) and numerous aggregation operators (AOs) have been added. According to the proposed method, the best alternative for lithium-ion battery (LIB) recycling is "a combination of mechanical shredding (MS), electrolyte extraction electrode (EE), dissolution (ED), and cobalt electrochemical reduction (CECR) [38].

Wu et al. present a decision assistance tool for assessing commercial (small-scale) energy storage devices. It then determines the best option(s) depending on the preferences of the users. The ranking findings clearly illustrate that user preferences have a significant influence on the recommended energy storage solutions [39]. For the thorough assessment of battery energy storage systems, Zhao et al suggested an fuzzy-MCDM integrated (multi-criteria decision making) model incorporating the Fuzzy-Delphi methodology, the Best-Worst method (BWM), and fuzzy-cumulative prospect theory (CPT). The empirical results reveal that Li-ion batteries are the preferred choice for micro-grid demonstration projects, followed by NaS batteries and NiMH batteries. Even if decision makers and investors have different risk preferences, the results show that when technological, considering environmental, economic, social, and performance factors, the Li-ion battery is still the best, followed by the NaS battery [40].

Yücenurşen and Sabancı investigated Different battery types for use in converting a small and light (600-1000 kg) ICE vehicle into an electric vehicle. The investigation was carried out to guarantee that this vehicle is acceptable for urban use and has a range of about 100 kilometers. Each battery technology's capacity is estimated to be around 15 kWh. When doing the techno-economic study of various battery types, it was taken into account that they delivered the required energy for about ten years. For comparison, seven different battery technologies (lead-acid, gel, Ni-Cd, Li-Ion, LiFePo₄, LiPo, and Ni-MH) were employed. Price assessment in US Dollars (\$), 10-year investment cost, weight and volume values, as well as weight and volume values necessary to create 1 kWh of energy, were included in the analysis tables. The analysis found that the cheapest technology for a 10-year lifetime was lead-acid technology. Lead-acid technology is 30% less costly than the second-cheapest gel technology and 82% less expensive than the most expensive technology, LiPo technology. The investigation discovered that the lightest technology was LiPo. This technique has been proven to be 85% lighter than gel technology. Aside from this information, tabular statistics on cycle life. self-discharge, benefits and downsides are provided [41].

The goal of this article is to select the best battery type for electric cars that also fits the distinctive criteria specified by experts, from among the five various battery types analyzed. The AHP approach, a multi-criteria decisionmaking process, will be researched to assess the weight of each criterion and then choose the best alternative among the given batteries. This study will discuss the electric car batteries issue and, with the help of expert judgment, by using integrated AHP-COPRAS, one of the multicriteria decision-making approaches, to select the best battery type.

2. MATERIAL AND METHODS

The battery type and attributes were analyzed using the AHP approach in this study, and a decision-making study was conducted. First and foremost, battery factors influencing battery selection were investigated for this aim. Nominal voltage, energy density, volumetric energy density, specific power, life cycle, and operating temperature are some of these properties [42]. In light of this knowledge, our decision-making criteria will be based on nominal voltage, energy density, volumetric energy density specific power, life cycle, operating temperature, and production cost, all of which are debatable for all battery kinds.

This section evaluates AHP by comparing different criteria and battery types based on expert assessments. A total of seven specialists were interviewed bilaterally. Two of the specialists are engineers who are industry professionals in their professions, and five of them are academics.

Analytical Hierarchy Process (AHP)

Thomas L. Saaty created the Analytical Hierarchy Process (AHP), a multi-criteria decision-making technique, in 1971 [43]. AHP; It is made out of previously understood discrete ideas and methods such as pairwise comparison, eigenvector-based weight derivation, and consistency measurement. Every element at every level is put through a two-way comparison with a target element [44]. When distributing weights, AHP has the option of allowing a hierarchical structure of criteria. which enables users to better concentrate on certain (primary) criteria and sub-criteria. A different construction might result in a different final ordering, thus this step is crucial. The decision maker should attempt to cluster these items similarly when building the AHP hierarchy with a lot of them [45].

The Analytical Hierarchy Process (AHP) is used in this study to assign weights to criteria. Figure 1 displays the battery type selection hierarchy framework, and Table 1 lists the importance



scale values along with their related meanings.

Figure 1. A hierarchical framework for selecting batteries.

Table 1. Importance scale values and definitions [4]	4]
------------------------------------------------------	----

Intensity of importance				
е	1	Equal Importance (EI)		
cal	3	Moderate Importance (MI)		
9 S	5	Strong Importance (SI)		
-1-	7	Very Strong Importance (VSI)		
aty	9	Extreme Importance (EI)		
Š	2, 4, 6, 8	Intermediate values		

The calculation of AHP involved utilizing the following mathematical formula. Specifically, formula 1 was applied to the components listed below the diagonal [46].

$$A = \begin{bmatrix} a_{12} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \dots & \ddots & \ddots & \ddots \\ \dots & \ddots & \ddots & \ddots \\ a_{n1} & a_{n2} & \dots & a_{nn} \end{bmatrix} \qquad a_{ji} = \frac{1}{a_{ji}} \qquad (1)$$

The matrix is created using the normalizing technique to evaluate the significance levels of the components, with a particular emphasis on equation 2 [47].

$$B_{i} = \begin{bmatrix} b_{11} \\ b_{21} \\ .. \\ .. \\ b_{n1} \end{bmatrix} \qquad bi_{j} = \frac{a_{ij}}{\sum_{i=1}^{n} a_{ij}}$$
(2)

Following that, matrix C is created by combining a collection of B-column vectors in a matrix structure, equal to the number of components. The Priority Vector, which displays the significance values, is then utilized to calculate the mathematical mean of matrix C's row components [44].

The number of elements and a coefficient (λ) known as Eigen Value is used to determine the Consistency Ratio (CR). To acquire the D column vector, initially compare the comparison

matrix A with the priority vector W.

$$C = \begin{bmatrix} c_{11} & c_{12} & \dots & c_{1n} \\ c_{21} & c_{22} & \dots & c_{2n} \\ \dots & \dots & \dots & \dots \\ c_{n1} & c_{n2} & \dots & c_{nn} \end{bmatrix} W = \begin{bmatrix} W_1 \\ W_2 \\ \dots \\ W_n \end{bmatrix} W_i = \frac{\sum_{j=1}^n c_{ij}}{n} \quad (3)$$
$$D = \begin{bmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \dots & \dots & \dots & \dots \\ a_{n1} & a_{n2} & \dots & \dots & a_{nn} \end{bmatrix} \times \begin{bmatrix} W_1 \\ W_2 \\ \dots \\ W_n \end{bmatrix} \quad (4)$$

Equation (5) is used to calculate E, and the arithmetic mean value (equation 6) yields the eigenvalue λ .

$$E_i = \frac{d_i}{w_i}$$
 (i=1,2,....n) (5)

$$\lambda = \frac{\sum_{i=1}^{n} E_{i}}{n}$$
(6)

After calculating the λ , it becomes possible to determine the Consistency Indicator (CI) using equation 7. In addition, the Consistency Ratio (CR) may be derived by dividing the calculated value by the equation (8) and comparing the CI value to the Random Consistency Index (RI) in Table 2.

$$CI = \frac{\lambda - n}{n - 1} \tag{7}$$

$$CR = \frac{CI}{RI} \tag{8}$$

Table 2. Values for the random consistency index [48]

The consistency test is considered complete after the CR is determined. The obtained data is consistent if the CR is less than 10%, showing that the comparison matrix is reliable. If the CR is equal to or more than 10%, the collected data is erratic, and the comparison matrix should be altered [19].

Table 3 was generated using experimental numbers from the literature for five distinct battery types.

Table 3. Comparison of Battery Types [49-55]								
Battery Property		Pb-Acid	Ni-C	Cd	NiMH	ZEBI	RA	Li-Ion
Nominal Voltage (V)		2.0	1.2		1.2	2.6		3.6
Energy Density (MJ/L) Volumetric energy density (Wh L ⁻¹)		0.36	1.08	8	1.55	0.32-0).43	0.83-3.6
Volumetric energy density (Wh L ⁻¹) Specific Power (W kg ⁻¹)		100	300		180-220	160		200-400
Specific Power (W kg ⁻¹)		180	200		200-300	155		200-430
Life-Cycle		1000	200	0	<3000	>1200)	2000
Operating Temperature (°C)		-15 to $+50$	-20	to +50	-20 to $+60$) +245	to + 350	-20 to $+60$
7	Tablo 4	. Experts' resp	onse	to the one	e-on-one ir	nterview		
Decision Variables	Exper	ts Cl	<i>C</i> 2	С3	<i>C4</i>	C5	С6	<i>C</i> 7
	<i>E1</i>	1	1/3	1/5	1/3	1/7	1	1/3
	<i>E2</i>	1	1/5	1/5	1/5	1/2	1	1/2
Nominal voltage C1	<i>E3</i>	1	1/5	1/7	1/5	1/7	/3	1/9
	<i>E4</i>	1	1/5	1/5	1/7	1/7	/3	1/7
	<i>E5</i>	1	1/3	1/3	1	1/3	1	1/3
	<i>E6</i>	1	1/3	1/7	1/3	1/2	1	1/9
	<i>E7</i>	1	1/5	1/7	1/5	1/7	/3	1/9
	E1	3	1	1	1/3	1/5	3	1/3
	<i>E2</i>	5	1	1	1	1/2	1	1/2
	<i>E3</i>	5	1	1	1	1/3	3	1/5
Energy Density C2	<i>E4</i>	5	1	1	1/3	1/3	3	1/5
	<i>E5</i>	3	1	1/3	1	1/3	3	1/3
	<i>E6</i>	3	1	1/7	1/3	3	1	1/9
	<i>E7</i>	5	1	1/3	1	1/3	3	1/5
	E1	5	1	1	1	1/3	3	1/3
Volumetric Energy Density C3	<i>E2</i>	5	1	1	1	1/2	1	1/2
	<i>E3</i>	7	3	1	1	1/3	3	1/5
	<i>E4</i>	5	1	1	1/3	1/3	3	1/5
	<i>E5</i>	3	3	1	3	1/2	3	1/2
	<i>E6</i>	7	7	1	1	3	3	1/7
	<i>E7</i>	7	3	1	1	1/3	3	1/5
	E1	3	3	1	1	1/3	5	1/3
	<i>E2</i>	5	1	1	1	1/2	1	1/2
	<i>E3</i>	5	1	1	1	1/3	3	1/5
Specific Power C4	<i>E4</i>	7	3	3	1	1	5	1
	<i>E5</i>	1	1	1/3	1	1/2	2	1/2
	<i>E6</i>	3	3	1	1	3	3	1/7
	<i>E7</i>	5	1	1	1	1/3	3	1/5
	E1	7	5	3	3	1	5	1/3
	<i>E2</i>	7	2	2	2	1	2	2
	<i>E3</i>	7	3	3	3	1	5	1/3
Life-cycle C5	<i>E4</i>	7	3	3	1	1	7	1
	<i>E5</i>	3	3	2	2	1	2	1/2
	<i>E6</i>	2	1/3	1/3	1/3	1	2	1/9
	<i>E7</i>	7	3	3	3	1	5	1/3
	<i>E1</i>	1	1/3	1/3	1/5	1/5	1	1/5
	<i>E2</i>	3	1	1	1	1/2	1	1/3
	<i>E3</i>	3	1/3	1/3	1/3	1/5	1	1/7
Operating Temperature C6	<i>E4</i>	3	1/3	1/3	1/5	1/7	1	1/7
	E5	l	1/3	1/3	1/2	1/2	1	1/3
	E6 E7	l	1	1/3	1/3	1/2	1	1/9
	E7 E1	3	1/3	1/3	1/3	1	1	1//
	EI E2	3	3	3	5	5 1/2	2	1
	E2 E2	1	2	2	2	1/2	5] 1
Production cost C7	E3 E4	9	2 2	5	5 1	3 1	7	1
r roauction cost C/	E4 E5	/	3	5	1	1	/	1
	ез Е4	3	5	27	2 7	2	5	1
	L0 F7	9	ש ק	1 5	/ 5	9 2	9 7	1 1
)	5	5	5	5	/	1

Table 5. Decision Matrix for citeria							
Decision Variables	C1	C2	C3	C4	C5	C6	C7
C1	1.0000	0.2489	0.1863	0.2776	0.2306	0.6245	0.1954
C2	4.0169	1.0000	0.5533	0.6245	0.4494	2.1918	0.2425
C3	5.3691	2.1145	1.0000	1.0000	0.5123	2.5643	0.2664
C4	3.6025	1.6013	1.0000	1.0000	0.5993	2.8002	0.3353
C5	5.1857	2.2250	1.9520	1.6685	1.0000	3.5424	0.4562
C6	1.8734	0.4562	0.3900	0.3571	0.3553	1.0000	0.1842
C7	6.1198	3.8328	3.7537	2.9827	2.1918	5.4285	1.0000
		Table 6.	Normalize	d matrix fo	r criteria		
Decision Variables	C1	C2	C3	C4	C5	C6	C7
C1							
CI	0.0368	0.0217	0.0211	0.0351	0.0432	0.0344	0.0729
C1 C2	0.0368 0.1479	0.0217 0.0871	0.0211 0.0626	0.0351 0.0789	0.0432 0.0842	0.0344 0.1207	0.0729 0.0905
C2 C3	0.0368 0.1479 0.1976	0.0217 0.0871 0.1842	0.0211 0.0626 0.1132	0.0351 0.0789 0.1264	0.0432 0.0842 0.0960	0.0344 0.1207 0.1413	0.0729 0.0905 0.0994
C2 C3 C4	0.0368 0.1479 0.1976 0.1326	0.0217 0.0871 0.1842 0.1395	0.0211 0.0626 0.1132 0.1132	0.0351 0.0789 0.1264 0.1264	0.0432 0.0842 0.0960 0.1123	0.0344 0.1207 0.1413 0.1543	0.0729 0.0905 0.0994 0.1251
C2 C3 C4 C5	0.0368 0.1479 0.1976 0.1326 0.1909	0.0217 0.0871 0.1842 0.1395 0.1938	0.0211 0.0626 0.1132 0.1132 0.2209	0.0351 0.0789 0.1264 0.1264 0.2109	0.0432 0.0842 0.0960 0.1123 0.1873	0.0344 0.1207 0.1413 0.1543 0.1952	0.0729 0.0905 0.0994 0.1251 0.1702
C2 C3 C4 C5 C6	0.0368 0.1479 0.1976 0.1326 0.1909 0.0690	0.0217 0.0871 0.1842 0.1395 0.1938 0.0397	0.0211 0.0626 0.1132 0.1132 0.2209 0.0441	0.0351 0.0789 0.1264 0.1264 0.2109 0.0451	0.0432 0.0842 0.0960 0.1123 0.1873 0.0665	0.0344 0.1207 0.1413 0.1543 0.1952 0.0551	0.0729 0.0905 0.0994 0.1251 0.1702 0.0687

 Table 5. Decision Matrix for criteria

COPRAS method

Zavadskas and Kaklauskas presented the COmplex Proportional ASsessment approach to the literature in 1996 [56]. It is used to rank and assess options while taking the benefit and cost features of the criterion into account [14]. The distinction between this approach and other MCDM methods is that the options may be compared to each other and their superiority over each other can be expressed as a percentage. The application of this method is as follows

i. Decion matrix created

$$A_{ij} = \begin{array}{cccc} a_{11} & \dots & a_{1p} \\ \vdots & \ddots & \vdots \\ a_{m1} & \dots & a_{mn} \end{array}$$

where m is alternative and p is criteria

ii. The elements of matrix A are used to compute the normalized decision matrix (X*). The elements of the normalized resolution matrix are represented by (x_{ij}^*) . Equation (9) was implemented to calculate (x_{ij}^*) .

$$\begin{aligned}
x_{ij}^{*} &= \frac{x_{ij}}{\sum_{i=1}^{m} x_{ij}} \\
(i = 1, ..., m \text{ and } j = 1, ..., p) \\
x_{11}^{*} & ... & x_{1p}^{*} \\
X^{*} &= \vdots & \ddots & \vdots \\
x_{m1}^{*} & ... & x_{mn}^{*}
\end{aligned} \tag{9}$$

iii. The weighting of the normalized decision matrix is determined using

equation 10 and the weights w_i.

$$n_{ij} = x_{ij}^* w_j \tag{10}$$

iv.
$$S_i^+$$
 and S_i^- values calculated
 S_i^+ the sum of utility criteria in a
weighted normalized decision
matrix
 S_i^- the sum of cost criteria in a

weighted normalized decision matrix

v. Equation 11 is used to compute relative significance values.

$$Q_{i} = S_{i}^{+} + \frac{\sum_{i=1}^{m} S_{i}^{-}}{S_{i}^{-} \sum_{i=1}^{m} \left(\frac{1}{S_{i}^{-}}\right)}$$
(11)

vi. Equation 12 is used to calculate the value of the performance index.

$$P_i = \left(\frac{Q_i}{Q_{max}}\right) * 100 \tag{12}$$

3. RESULT AND DISCUSSION

Seven experts were interviewed one-on-one and questions were posed Table 4 has been prepared. By taking the geometric mean of the values given in Table 4, the decision matrix (Table 5) was generated.

In order to normalize the decision matrix (table 5) equation 2 was used. Results tabulated in Table 6.

Once the normalization was completed, the eigenvector, eigenvalue, consistency index and consistency ratio were determined by using equations 3 to 8. The results were tabulated in Table 7.

The CR is less than 10%, implying that the data acquired is consistent, demonstrating that the matrix used for comparison is reliable. The weighted outcomes of the criterion calculations are tabulated in Table 8.

where wC1: weight of Nominal voltage, wC2: weight of Energy Density, wC3: weight of Volumetric Energy Density, wC4: weight of Specific Power, wC5: weight of Life-cycle, wC6: weight of Operating Temperature, wC7: weight of Production cost

Ranking the batteries with COPRAS

After the weights are determined by AHP, a ranking will be made between the alternatives with the COPRAS method. To appeal to the consumer (buyer), the manufacturing cost requirement was also added, and expert opinions were sought.

In addition to the values given in the literature, linguistic evaluation such as expensive, very expensive, given verbally, is given a 1 to 9 scale to be close to the Saaty scale.

Table 7. The results of the eigenvector, eigenvalue, consistency index and consistency ratio

eigen vector	eigenvalue	λmax	CI	CR
0.037884	0.271082	7.30908	0.0515	0.0382
0.095996	0.698679			
0.136866	1.007783			
0.129048	0.945755			
0.195612	1.443963			
0.05548	0.403517			
0.349114	2.577456			

			Table 8. We	eight of	the criteria		
	WC1	WC2	WC3	WC4	WC5	WC6	WC7
	0.0379	0.0960	0.1369	0.1291	0.1956	0.0555	0.3491
			Table 9.	Product	ion cost		
		Pb-Acid	Ni-Cd	I	NiMH	ZEBRA	Li-Ion
Produ	uction Cost	Cheap	Over costing	g (Over costing	Average	Over costing
			Table 10.	Linguis	tic Scale		
			Linguistic		Scale		
			Very Cheap		1		
			Cheap		3		
			Average		5		
			Expensive		7		
			Very Expens	sive	9		

To evaluate the batteries the chosen criteria are coded as: C_1 . Nominal voltage criteria, C_2 . Energy Density criteria, C_3 . Volumetric Energy Density, C_4 . Specific Power criteria, C_5 . Lifecycle criteria, C_6 . Operating Temperature criteria, C_7 . Production cost criteria

The decision matrix was created using literature [49-55]. The alternatives of batteries were symbolized as Pb-Acid: A1, Ni-Cd: A2, Ni-Mh: A3, Zebra: A4, and Li-ion: A5, respectively. While creating the decision matrix operating temperature is given as a range so the maximum temperature is chosen for evaluation since it is considered a utility. In addition to this assumption, Life-cycle criteria were given for the battery Ni-Mh as <3000 and also for the ZEBRA type battery >1200 these values were

taken as 2900 and 1300, respectively.

Table 11. Decision matrix for evaluating alternative

		b	atterie	S			
Altownation	Crite	eria					
Allernalives	C_{l}	C_2	Сз	C_4	C_5	C_6	C_7
A_1	2	35	100	180	1000	50	3
A_2	1.2	80	300	200	2000	50	9
A3	1.2	95	220	300	2900	60	9
A_4	2.6	120	160	155	1300	350	5
A5	3.6	250	400	430	2000	60	9

In order to normalize the decision matrix (Table 11) equation 9 was used and the results were tabulated in Table 12.

The weight of the criteria that were calculated by the AHP method was used to calculate the weighted normalized matrix by using equation 10 and the results are tabulated in Table 13.

_	1 a	ble 12. \mathbf{N}	rmanzed	inzed matrix for alternative batteries				
	C_1	C_2	Сз	<i>C</i> ₄	<i>C</i> 5	<i>C</i> ₆	<i>C</i> ₇	
-	0.1887	0.0603	0.0847	0.1423	0.1087	0.0877	0.0857	
	0.1132	0.1379	0.2542	0.1581	0.2174	0.0877	0.2571	
	0.1132	0.1638	0.1864	0.2372	0.3152	0.1053	0.2571	
	0.2453	0.2069	0.1356	0.1225	0.1413	0.6140	0.1429	
	0.3396	0.4310	0.3390	0.3399	0.2174	0.1053	0.2571	
		Table	13. Weig	ghted norr	nalized m	atrix		
C1	C ₂	C ₃		C4	C5	C 6	C 7	
0.0071	0.005	58 0.0	116	0.0184	0.0213	0.004	49 0.0299	
0.0043	0.013	.0.0	348	0.0204	0.0425	0.004	49 0.0898	
0.0043	0.015	57 0.0	255	0.0306	0.0617	0.005	58 0.0898	
0.0093	0.019	9 0.0	186	0.0158	0.0276	0.034	0.0499	
0.0129	0.041	4 0.0	464	0.0439	0.0425	0.005	58 0.0898	

Table 12. Normalized matrix for alternative batteries

The criterion C1 to C6 are utility criteria and C7 is the cost criteria. Si+ and Si- values are calculated where Si+ the sum of utility criteria in a weighted normalized decision matrix and Si- the sum of cost criteria in a weighted normalized decision matrix. Si+ and Si- values were used to compute the relative significance values. Equation 11 is used to compute relative significance values (Qi). And the gained results are tabulated in Table 14.

 Table 14. Relative Significance values of the alternatives

Alternative	S_{i}^{+}	Si	1/Si	Q_i
A ₁	0.0690	0.0299	33.4183	0.2033
A_2	0.1201	0.0898	11.1394	0.1649
A 3	0.1436	0.0898	11.1394	0.1884
A 4	0.1252	0.0499	20.0510	0.2058
A ₅	0.1929	0.0898	11.1394	0.2376

Relative significance values were used to calculate the performance indices. Performance indices were calculated by using Equation 12 and the computed results are tabulated in Table 15. The performance index shows the ranks of alternatives.

_ _

Tab	le 15	. Performance inde	ex
_	Perf	formance index	
-	P 1	85.5551	
	P ₂	69.3848	
	P 3	79.2800	
	P ₄	86.6036	
_	P5	100.00	
Tab	le 16	6. Ranks of batterie	es
Alternative	Per	rformance index	Rank
A_{I}	85.	5551	3
A_2	69.	3848	5
A_3	79.	2800	4
A_4	86.	6036	2

Once the performance index is calculated the ranks of the alternatives which are tabulated in Table 16 come to the fore.

where A₁: Pb-Acid, A₂: Ni-Cd, A₃:Ni-Mh, A₄: Zebra, A₅: Li-ion, respectively.

The calculations show that alternative A5, with the highest performance index, is the best option, while alternative A2, with the lowest performance index, is the worst. In terms of battery preferences, the final ranking is as follows: Li-ion, Zebra, Pb-Acid, Ni-Mh, and Ni-Cd, in that order. A decision has been made to encourage the development and deployment of alternative Li-ion, which has the greatest performance index.

4. CONCLUSION

The environmental damage of internal combustion engines threatens the balance of the world. For this reason, scientists have started to search for renewable alternative vehicles in terms of environmental impact and health. Electric vehicles have grown in popularity among researchers because they are safe, ecologically benign, and long-lasting.

The analytical hierarchy technique was used to examine the properties of five distinct battery types (Pb-Acid, Ni-Cd, NiMH, ZEBRA, and Li-Ion) in this study. The present study examined seven distinct battery properties (nominal voltage, energy density, volumetric energy density, specific power, life cycle, operating temperature, and production cost) and five different battery types. The relevance of attributes is given as manufacturing cost, lifecycle, volumetric energy density, specific power, energy density, operating temperature, and nominal voltage, according to determined weighted results using AHP. Based on this point, the COPRAS method assessment of five distinct battery types revealed that Li-Ion is the best-suited battery type and Ni-Cd is the least favorable among the analyzed battery kinds. In prospective research, different attributes and battery kinds can be produced. Similarly, the outcomes may be compared using various multicriteria decision-making procedures.

Acknowledgement:

The authors wish their sincere thanks to Prof. Kadir Aydın, Assoc. Prof. Gökhan Tüccar, Assoc. Prof. Erinç Uludamar, Assist. Prof. Tayfun Özgür, Assist. Prof. Tahsin Köroğlu, Enes Karabıyık, and Bengü Üst for their valuable answers to the questionnaire.

CRediT authorship contribution statement

Aslı Abdulvahitoğlu: Conceptualization, Formal Analysis, Methodology, Visualization, Writing - original draft, Writing - review & editing. Gözde Ekmekçi Güçlüten: Investigation, Resurces, Writing - Original Draft

5. References

1. Verma S., Mishra S., Gaur, A., Chowdhury S., Mohapatra S., Dwivedi G. and Verma P. A comprehensive review on energy storage in a hybrid electric vehicle. Journal of Traffic and Transportation Engineering (English Edition), 2021.

2. Troy R. Hawkins, Ola Moa Gausen, Anders Hammer Strømman, Environmental impacts of hybrid and electric vehicles—a review, Int. J. Life Cycle Assess. 17(8), 997– 1014, 2012.

3. IEA, Global EV Outlook 2022, Technical Report, International Energy Agency, Paris, France, 2022, https://www.iea.org/reports/global-ev-outlook-2022, Accessed August 2023.

4. TurkStadt https://www.tuik.gov.tr/ accessed August 223

5. Özbay, H., Közkurt, C., Dalcalı, A., Tektaş, M. Geleceğin Ulaşım Tercihi: Elektrikli Araçlar. Akıllı Ulaşım Sistemleri ve Uygulamaları Dergisi, 3 (1), 34-50, 2020.

6. Sezen B. and İşler A.U. Elektrikli

Araçların Mevcut Durumu, Tercih Edilme Ve Edilmeme Sebepleri. Turkish Journal of Marketing, 2(2), 82-103, 2017

7. Winter M. and Brodd R.J. What are Batteries, Fuel Cells, and Supercapacitors? Chemical Reviews, 105 (3), 1021-1021, 2005

8. Kerem, A. Elektrikli Araç Teknolojisinin Gelişimi ve Gelecek Beklentileri. Mehmet Akif Ersoy Üniversitesi Fen Bilimleri Enstitüsü Dergisi, 5 (1), 1-13, 2014.

9. Özcan, Ö. F., Karadağ, T., Altuğ, M., Özgüven, Ö. F. Elektrikli Araçlarda Kullanılan Pil Kimyasallarının Özellikleri ve Üstün Yönlerinin Kıyaslanması Üzerine Bir Derleme Çalışması. GU J Sci, Part A, 8(2), 276-298, 2021.

10. Muratoğlu Y. and Alkaya A. Elektrikli Araç Teknolojisi ve Pil Yönetim Sistemi-İnceleme. Elektrik Mühendisliği, 458, 10-14, Eylül 2016.

11. Budde-Meiwes H, Drillkens J, Lunz B, et al. A review of current automotive battery technology and future prospects. Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering, 227(5):761-776. 2013

12. Moralı, U. & Erol, S.,18650 lityum-iyon ve 6HR61 nikel-metal hidrit tekrar şarj edilebilir pillerinin elektrokimyasal empedans analizi. Gazi Üniversitesi Mühendislik Mimarlık Fakültesi Dergisi, 35 (1), 297-310. 2020.

13. Miao Y, Hynan P, von Jouanne A, Yokochi A. Current Li-Ion Battery Technologies in Electric Vehicles and Opportunities for Advancements. Energies; 12(6):1074, 2019

14. Demir G., Özyalçın A. T. Bircan H. Çok Kriterli Karar Verme Yöntemlerive ÇKKV Yazılımı ile Problem Çözümü, Nobel Yayınevi, 382 sf., Mayıs 2021.

15. Alojaiman B., A Multi-Criteria Decision-Making Process for the Selection of an Efficient and Reliable IoT Application, Processes; 11(5):1313,2023.

16. Halder S., Roy M.B., Roy P. K., Sedighi M., Groundwater vulnerability assessment for drinking water suitability using Fuzzy Shannon Entropy model in a semi-arid river basin, CATENA, Volume 229, 107206, 2023

17. Geetha S., Jeon J.H., Stratified network mapping decision making technique based

decision support framework for R&D budget allocation in South Korea, Socio-Economic Planning Sciences, Volume 87, Part B, 101579, 2023.

18. Annamalai, P., Dhavamani, C. Experimental Investigation on Machining of Recycled Aluminum Alloy Metal Matrix Composite in ECMM. Trans Indian Inst Met 76, 1831–1839, 2023.

19. Abdulvahitoglu A., Kilic M., A new approach for selecting the most suitable oilseed for biodiesel production; the integrated AHP-TOPSIS method, Ain Shams Engineering Journal, 13(3), 101604, 2022.

20. Abdulvahitoğlu, A., Abdulvahitoğlu, A., Kılıç, M. Elektrikli Araç Bataryalarının Bütünleşik Swara-Topsis Metodu ile Değerlendirilmesi. Çukurova Üniversitesi Mühendislik Fakültesi Dergisi, 37 (4), 1061-1076, (2022).

21. Fossile, D.K.; Frej, E.A.; da Costa, S.E.G.; de Lima, E.P.; de Almeida, A.T. Selecting the most viable renewable energy source for Brazilian ports using the FITradeoff method. J. Clean. Prod., 260, 121107, 2020.

22. Siksnelyte-Butkiene, I.; Zavadskas,
E.K.; Streimikiene, D. Multi-Criteria Decision-Making (MCDM) for the Assessment of Renewable Energy Technologies in a Household: A Review. Energies, 13, 1164,2020.
23. Ebbs-Picken T, Da Silva C. M., Amon C.

23. Ebbs-Picken T, Da Silva C. M., Amon C. H., Design optimization methodologies applied to battery thermal management systems: A review Journal of Energy Storage 67, 107460, 2023.

24. Lamya Albraheem, Lama AlAwlaqi, Geospatial analysis of wind energy plant in Saudi Arabia using a GIS-AHP technique, Energy Reports, 9, 5878-5898, 2023.

25. Brodny J., Tutak M., Assessing the energy security of European Union countries from two perspectives – A new integrated approach based on MCDM methods, Applied Energy, 347, 121443, 2023.

26. Äkräs L., Vahvaselkä M., Silvenius F., Seppälä J., Ilvesniemi H., A multi-criteria decision-making framework and analysis of vegetable oils to produce bio-based plastics, Industrial Crops and Products, Volume 188, Part A, 115584, 2022.

27. Kang D., Jaisankar R., Murugesan V., Suvitha K., Narayanamoorthy S., Omar H. A, Arshad N. I., Ahmadian A., A novel MCDM approach to selecting a biodegradable dynamic plastic product: a probabilistic hesitant fuzzy set-based COPRAS method, Journal of Environmental Management, Volume 340, 17967, 2023.

28. Daniel, M., Ahammed, M.M. & Shaikh,
I.N. Selection of Greywater Reuse Options
Using Multi-criteria Decision-making
Techniques. Water Conserv Sci Eng 8, 2, 2023.
29. Abdulvahitoğlu, A. Prioritization of risk
factors causing juvenile delinquency with
SWARA Method: A Case Study from Türkiye.
Türk İdare Dergisi, 95(496):39-61, 2023

30. Ecer F., Küçükönder H., Kaya S. K., Görçün Ö.F., Sustainability performance analysis of micro-mobility solutions in urban transportation with a novel IVFNN-Delphi-LOPCOW-CoCoSo framework, Transportation Research Part A: Policy and Practice, Volume 172, 103667, 2023.

31. Deveci M., Pamucar D., Gokasar I., Zaidan B. B., Martinez L., Pedrycz W., Assessing alternatives of including social robots in urban transport using fuzzy trigonometric operators based decision-making model, Technological Forecasting and Social Change, 194, 122743, 2023.

32. Can G. F., Toktaş P. and Pakdil F., Six Sigma Project Prioritization and Selection Using AHP–CODAS Integration: A Case Study in Healthcare Industry, in IEEE Transactions on Engineering Management, 70(10), 3587-3600, 2023.

33. Akhoundi, B., Modanloo, V. A multicriteria decision-making analysis on the extrusion-based additive manufacturing of ABS/Cu composites. Int J Interact Des Manuf 17, 1995–2003, 2023.

34. Nayagam, V.L.G., Suriyapriya, K., Jagadeeswari, M. A Novel Similarity Measure Based on Accuracy Score of Conventional Type of Trapezoidal-Valued Intuitionistic Fuzzy Sets and Its Applications in Multi-criteria Decision-Making Problems. Int J Comput Intell Syst 16, 106, 2023.

35. Lamrini, L., Abounaima, M.C. & Talibi Alaoui, M. New distributed-topsis approach for multi-criteria decision-making problems in a big data context. J Big Data 10, 97,2023.

36. Loganathan M.K., Mishra B., Tan C.M., Kongsvik T. and Rai R.N. Multi-Criteria decision making (MCDM) for the selection of Li-Ion batteries used in electric vehicles (EVs). Materials Today: Proceedings 41, 1073-1077, 2021.

37. Sonar H.C. and Kulkarni S.D. An Integrated AHP-MABAC Approach for Electric Vehicle Selection. Research in Transportation Business & Management, 41,100665, 2021.

38. Chakraborty S., Saha A. K., Selection of optimal lithium ion battery recycling process: A multi-criteria group decision making approach, Journal of Energy Storage, 55, Part B, 105557, 2022.

39. Wu Z., Khalilpour K., Hämäläinen R. P., A decision support tool for multi-attribute evaluation of demand-side commercial battery storage products, Sustainable Energy Technologies and Assessments, Volume 50, 2022, 101723.

40. Zhao H., Guo S., Zhao H., Comprehensive assessment for battery energy storage systems based on fuzzy-MCDM considering risk preferences, Energy, 168, 450-461, 2019.

41. Yücenurşen, A. & Samancı, A. Battery selection criteria for electric vehicles: technoeconomic analysis. International Journal of Automotive Engineering and Technologies, 12(2), 65-74, 2023.

42. Liang Y., Zhao C., Yuan H., Chen Y., Zhang W., Huang J., Yu D., Liu Y., Titirici M., Chueh Y., Yu H. and Zhang Q. A review of rechargeable batteries for portable electronic devices. Wiley Online Library, 1(1), 6-32, 2019.
43. Ünal, Ö. F. Analitik Hiyerarşi Prosesi Ve Personel Seçimi Alanında Uygulamaları. Uluslararası Alanya İşletme Fakültesi Dergisi, 3 (2), 18-38, 2011.

44. Abdulvahitoğlu A. Using Analytic Hierarchy Process for Evaluating Different Biodiesels as an Alternative Fuel. Çukurova Üniversitesi Mühendislik Mimarlık Fakültesi Dergisi, 33 (3), 177 – 186, 2018.

45. Ishizaka A., Labib A. Review of the main developments in the analytic hierarchy process, Expert Systems with Applications, 38(11), 14336-14345, 2011.

46. Alonso, J.A., Lamata, M.T. Consistency in the Analytic Hierarchy Process: A New Approach. International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems 14, (04), 445-459,2006. 47. Davras, G. M. & Karaatlı, M., Otel İşletmelerinde Tedarikçi Seçimi Sürecinde Ahp Ve Bahp Yöntemlerinin Uygulanması. Hacettepe Üniversitesi İktisadi ve İdari Bilimler Fakültesi Dergisi, 32 (1), 87-112, 2014.

48. Awasthi, A., Satyaveer S. Chauhan. Using AHP and Dempster Shafer Theory for Evaluating Sustainable Transport Solutions, Environmental Modelling & Software 26(6):787-796, 2011.

49. Hadjipaschalis, I., Poullikkas, A., & Efthimiou, V. Overview of current and future energy storage technologies for electric power applications. Renewable and Sustainable Energy Reviews, 13(6-7), 1513-1522, 2009.

50. Cano, Z. P., Banham, D., Ye, S., Hintennach, A., Lu, J., Fowler, M. and Chen, Z. Batteries and fuel cells for emerging electric vehicle markets. Nature Energy, 3(4), 279-289, 2018.

51. Perujo, A., Grootveld, G. V., and Scholz, H. Present and future role of battery electrical vehicles in private and public urban transport. In: Z. Stević (Eds), New Generation of Electric Vehicles (pp. 3-25). Intech, 2012.

52. Khaligh, A. and Li, Z. Battery, ultracapacitor, fuel cell, and hybrid energy storage systems for electric, hybrid electric, fuel cell, and plug-in hybrid electric vehicles: State of the art. IEEE Transactions on Vehicular Technology, 59(6), 2806-2814, 2010.

53. Soloveichik, G. L. Battery technologies for large-scale stationary energy storage. Annual Review of Chemical and Biomolecular Engineering, 2(1), 503-527, 2011.

54. Vidyanandan, K. V. Batteries for Electric Vehicles. IEEE, 2019.

55. S. M. Sundaram, M. Kulkarni and V. Diwakar, "Management of large format liion batteries," 2015 IEEE International Transportation Electrification Conference (ITEC), Chennai, India, 2015, pp. 1-7, doi: 10.1109/ITEC-India.2015.7386883.

56. Hezer, S., Gelmez, E., & Özceylan, E. Comparative analysis of TOPSIS, VIKOR and COPRAS methods for the COVID-19 Regional Safety Assessment. Journal of infection and public health, 14(6), 775-786, 2021.