PAPER DETAILS

TITLE: PARKINSONNET: CLASSIFICATION PARKINSON'S DISEASE MODEL BASED ON NOVEL DEEP LEARNING STRUCTURE AUTHORS: Saif Aljumaili PAGES: 259-276

ORIGINAL PDF URL: https://dergipark.org.tr/tr/download/article-file/3503228

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

PARKINSONNET: CLASSIFICATION PARKINSON'S DISEASE MODEL BASED ON NOVEL DEEP LEARNING STRUCTURE

Saif AL-JUMAILI¹

¹Engineering and Architecture Faculty, Altınbaş University, İstanbul, Türkiye, <u>saifabdalrhman@gmail.com</u> (¹https://orcid.org/0000-0001-7249-4976)

Received: 31.10.2023	Research Article
Accepted: 01.11.2023	pp.259-276
Published: 31.12.2023	
*Corresponding author	DOI: 10.53600/ajesa.1382806

Abstract

Neuroimaging, particularly magnetic resonance imaging (MRI), has advanced significantly in recent decades and has played a significant sessional part in studying brain functions and diseases. MRI images, combined with unique ML approaches and developed tools during these years, have opened up new opportunities for diagnosing neurological illnesses. However, due to the apparent symptoms that are similar to each other, brain illnesses are regarded as difficult to precisely detect. This research examines a newly developed algorithm (ParkinsonNet) to classify Parkinson's disorder into two unique classes which are Control (healthy) and Parkinson's (PD), Convolutional neural networks (CNN) are one of the deep learning methodologies used in this procedure. CNN is one way that may be used to classify a range of brain illnesses such as Parkinson's. We employed a freshly constructed CNN technique from scratch, and we got 97.9% accuracy which is considered outstanding compared with recently published articles using the same dataset. **Keywords: Parkinson's Disease, CNN, MRI Image, Deep Learning.**

BAŞLIK

Özet

Son birkaç on yılda nörogörüntüleme, özellikle de manyetik rezonans görüntüleme (MRI), beyin fonksiyonları ve hastalıklarının incelenmesinde önemli bir oturumsal rol oynamıştır. Bu yıllarda benzersiz makine öğrenimi yaklaşımları ve geliştirilen araçlarla birleştirilen MRI görüntüleri, nörolojik hastalıklarını teşhisinde yeni fırsatlar yarattı. Ancak belirtilerin birbirine benzer olması nedeniyle beyin hastalıklarının kesin olarak tespit edilmesi zor kabul edilmektedir. Bu araştırma, Parkinson hastalığını Kontrol (sağlıklı) ve Parkinson (PD) olmak üzere iki benzersiz sınıfa ayırmak için yeni geliştirilen bir algoritmayı (ParkinsonNet) incelemektedir; bu yöntem, derin öğrenme yaklaşımlarından biri olan Evrişimsel sinir ağları (CNN). CNN, Parkinson gibi çeşitli beyin hastalıklarını sınıflandırmak için kullanılabilecek yollardan biridir. Yeni oluşturulmuş bir CNN tekniğini sıfırdan kullandık ve aynı veri kümesini kullanan yakın zamanda yayınlanan makalelerle karşılaştırıldığında olağanüstü kabul edilen %97,9 doğruluk oranı elde ettik. **Anahtar Kelimeler: Parkinson hastalığı (PD), Evrişimli Sinir Ağı (CNN), MRI Görüntüsü, Derin Öğrenme.**

1. Introduction

The human brain may face lots of diseases that affect its control ability and may lead to uncontrol action and judgments. For instance, Alzheimer's disease (AD)(Al-Jumaili et al. 2023), Common neurological illnesses include Parkinson's disease (PD) and schizophrenia (SZ) which cause a disruption in brain function (Tolosa, Wenning, and Poewe 2006; Danielyan and Nasrallah 2009; Al-Jumaili et al. 2023; Al-azzawi et al. 2022). PD is considered a hazardous illness that, if detected in time, can be eradicated or, in the worst situation, slowed (Fontana et al. 2017; Leparulo et al. 2019). In this study, we explore the difficulties in classifing PD and highlight the potential applications of deep learning algorithms. PD is a chronic, progressive neurological disorder characterized by a lack of dopamine in the brain's substantia nigra. Figure 1 depicts the location of the substantia nigra in the brain as well as the substantia in a healthy individual and a Parkinson's disease patient. Our disease is more frequent among the aged people, generating stride and posture alterations that may increase the risk of falling and lead to mobility issues.

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

So, the result, it interferes with daily activities and reduces the quality of life for patients and their families (Hughes et al. 2002).



Figure 1. A healthy subject (top right) and a PD (bottom right) have their substantia-nigra images compared.

PD symptoms usually appear gradually over time. Due to the disease's variety, the symptoms of progression differ from one another. This makes detecting the illness in its first phases exceedingly challenging. The current clinical diagnosis of Parkinson's disease is primarily clinical; however, imaging can assist in confirming dopamine degradation and distinguish Atypical parkinsonism is a kind of Parkinson's disease (Stoessl, Lehericy, and Strafella 2014). Furthermore, the severity of the illness is assessed using the Unified Parkinson Illness Rating Scale (UPDRS), This comprises a log of various patient motions taken at regular intervals. UPDRS data and the images are utilized for diagnosis and research allowing us to design tasks that take advantage of deep learning capabilities while reducing the manual work required to analyze this data. Doctors employ a variety of tests and imaging to confirm Parkinson's disease because there is no standardized method. We offer an overview of the many forms of data collected and develop a classification/prediction problem to aid in diagnosis.

Several neuroimaging approaches, including MRI and CT techniques, help to identify these illnesses early identification, deep learning (DL)-based analytic algorithms have been created (Islam and Zhang 2018; Shatte, Hutchinson, and Teague 2019; Salvatore et al. 2014; Mathew, Vivek, and Anurenjan 2018), as well as to develop appropriate treatment plans (Mahmud and Vassanelli 2016, 2019; Poldrack, Gorgolewski, and Varoquaux 2019). In the last era, ML had been the magic wand that applied successfully in various fields and with different needs such as image analysis (Ali, Kaiser, and Mahmud 2019), disease detection (Noor et al. 2019; Miah et al. 2021), data mining (Mahmud et al. 2018; Mahmud et al. 2021), etc. Moreover, DL has a noticeable success when dealing with neurological when researchers attempted to employ DL-based for the diagnosis of brain disorders from MRI scans (Islam and Zhang 2020; Lei et al. 2020; Chand et al. 2020).

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

For much over a decade, medical issues have been solved using neural networks. However, as processing power has increased in the last few years,

, CNN has found its way into the medical profession due to its high sensitivity in identifying tumors and other abnormalities (Thaha et al. 2019; Mahmoudi et al. 2022; Kumari and Barpanda 2023; Moujahid, Cherradi, and Bahatti 2020). In PD case, medical imaging entails the use of various scans such as MRI, PET, and DAT-scan, each of which should be equipped with its own trained model to be relevant in PD diagnosis. The next reviews summarize various perspectives. For instance, one of them tries to combine the uses of machine learning and big data to investigate mental health (Shatte, Hutchinson, and Teague 2019). Moreover, several ML-based tasks have been investigated using connectome data from MRI in order to improve the diagnosis of neurological diseases (Neromyliotis et al. 2022). In addition, researchers in (Litjens et al. 2017), analyzed various medical images such as neuro, pulmonary, and pathology and applied them to DL. The authors of (Gottapu and Dagli 2018) investigated the use of DL to improve understanding and diagnosis of Parkinson's illness. In the same matter, researchers in (Lee et al. 2018), used Voxel-based morphometry which is an automatic volume method, used mainly to compare differences in brain volume between healthy and patient people. Huang et al. (Huang et al. 2021), suggested an unsupervised feature selection strategy for manifold learning based on longitudinal multimodal data. The method's fundamental idea is to compute the similarity matrix and discriminant features adaptively using joint embedding and sparse regression. Additionally, Cigdem et al. (Cigdem and Demirel 2018), They created 3D montages for GM (grey matter) and WM (white matter) tissues by combining various variables and GM, WM, and a two-sample t-test procedure to classify Parkinson. Kollias et al. (Kollias et al. 2018), They suggested a DNN architecture that included CNN for deriving rich internal representations from input data and a bidirectional-LSTM/gated recurrent units (GRU RNNs)-based RNN for analyzing the temporal progression of the inputs and giving final predictions. The ResNet and ReLU architectures were used to create a hybrid supervised and unsupervised learning approach. They helped to create a new database that was utilized for training, testing, and verifying the suggested systems. Norwitz et al. (Norwitz et al. 2020), They compared the effects of immediate administration of a ketone ester drink and a tastematched, carbohydrate-based control drink on endurance exercise performance in 14 participants with Parkinson's disease (40). Within 30 minutes of intake, the ketone ester drink increased participants' -HB levels to a mean of 3.5 mmol/L. When compared to the isocaloric placebo drink, consumption of the ketone ester drink was related to a 24% increase in exercise endurance capacity, suggesting that ketone ester supplementation has the potential to alter motor function in Parkinson's disease. However, authors face throughout the diagnosing of the disease it involves multiple features such as motor functions, dopamine concentration, and many other clinical tests so it is considered a Challenge. Therefore, examining only one attribute to Understand the condition is insufficient as there are several brain-related disorders with comparable symptoms. Based on the previous accuracy values obtained from the different types of studies. Thus, we propose a novel convolutional neural network to increase the accuracy further. And to provide a tool that can help the health sector classify Parkinson's diseases. Our paper Sections are structured like this: Section 2 uses strategies, while Section 3 offers the work results. Finally, the conclusion is listed in Section 4.

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

2. Methodology

2.1. Brain MRI Dataset

The primary motivation for this project was to provide an ensembled framework for Parkinson's disease classification; the MRI dataset used came from Kaggle's public databases (Kabir 2022). This dataset contains 6477 MRI pictures, including 3010 MRI slices for healthy people, 906 MRI slices for Parkinson's disease, and 2561 MRI slices for Alzheimer's illness. The full set of MRI slices is in PNG format, and their size was changed to 224 X 224 pixels throughout the work. We used here just two classes: the PD and the healthy condition as presented in Figure 2.



Figure 1. MRI images of the two classes of the dataset used, (A) the healthy, and (B) for PD.

2.2. Design Convolutional Neural Network (CNN)

CNN is a deep learning approach, are designed particularly for image analysis with two-dimensional data (Al-Jumaili et al. 2022). CNN is built on layers, each with its own learning process and outputs that are fed into the following levels. CNN is a learning algorithm that employs a raw input picture as its foundation. The standard structure of CNN is often divided into two basic components: feature extraction and classification. To collect characteristics, several types of layers are used to extract hidden data from MRI images, which play an important role since they have a major influence on the precision of classification results. Following that, the classifier will take all of the features extracted from it and split them into the right classifications. Convolution is the most important stage in CNN approaches since it is responsible for detecting traits and applying filters. Strides and the number of filters are two extremely important elements that have a substantial influence on the output of the convolutional operation, with stride defined as the space that separates two pixels and a number of filters defined as the number of features in the feature map (Haq et al. 2022). Two functions, f, and G, are mathematically merged to produce H(t), where H represents the entire amount of overlap of only one function, f(T), as it moves over the other criterion, G (Yamashita et al. 2018). This is demonstrated in the equation outlined below.

$$H(t) = \int_{-\infty}^{\infty} f(T)G(t-T)dT$$

Whenever used, H = f * G

AURUM MÜHENDİSLİK SİSTEMLERİ VE MİMARLIK DERGİSİ

AURUM JOURNAL OF ENGINEERING SYSTEMS AND ARCHITECTURE

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023



auril

Figure 3. (a) Input Matrix (b) Kernel Matrix (c) Outcome Matrix.

As shown in Figure 4 below, each of the six blocks of the convolution layer used in our proposed approach for deriving characteristics from MRI images has a (convolution Layer, batch Normalisation Layer, clipped Relu Layer, and MaxPooling Layer). The technique normally starts in the upper left corner, where the kernel matrix we utilized was 3x3 fixed for all Convolution layers yielding a result comparable to that seen in Figure 3. The kernel matrix 3x3 is then used again, but this time it is moved one column to the right owing to the Stride set (1x1), encompassing the full picture input. The activation function is critical in transforming linear input data to nonlinear output in order to speed up training and reduce network sensitivity. Despite the fact that ReLU cannot simultaneously activate all of the neurons in a cell, it is one of the most extensively used activation methods. To keep the final output from growing too large, we employed a Clipped Rectified Linear Unit (clipped Relu Layer) with a limit approach. All input less than zero is converted to zero, and any value more than the ceiling is made to match the clipping ceiling, which is equal to 10. Furthermore, utilizing Max Pooling boosted the precision ratio by pooling the map's convolutional features to reach the highest feasible average value. Furthermore, in the classification portion, input characteristics were sent to three sets of fully connected layers, each of which was preceded by a dropout layer that was (0.5) to prevent overfitting that happened in the model and followed by all features retrieved by convolution layers. The last block consisted of the Fully Connected Layer, SoftMax Layer, and Classification Layer.



Figure 4. An outline of out technique

11

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

2.3. Evaluation Metrics

Actual Class

In accordance with the results that confusion matrix have and illustrated in Table 1, we used a number of assessment metrics to evaluate the efficacy of our proposed model. Table 1 summarises the accurate and wrong values assigned by the classifier for the predictions. These metrics are used to analyze and test the model's efficacy, such as accuracy.

Classes Name		Predicted Class	
	Control	130	1

PD

2

 Table 1. confusion matrix outcome.

Generally, Confusion matrices are extensively used since they offer a more exact image of a model's efficiency than classification accuracy. Moreover, precision, sensitivity, and specificity were evaluated using the means as equations shown in Table 2. Accuracy was defined by the proportion of forecasts in the overall dataset that were correct. The total number of correct positive predictions from each positive prediction is used to calculate recall or sensitivity. While, precision, also known as confidence, is the probability that an actual number will be larger than the total of anticipated positives. Furthermore, the balance of precision and memory is represented by a harmonic, sometimes known as the F1-Score, the combination of precision and recall is represented. Using F1-Score is a secure technique to get a clear sense of the results we received.

 Table 2. The equations used to calculate the results.

$Accuracy = \frac{TP + TN}{TP + FP + TN + FN}$
$Recall = Sensitivity = \frac{TP}{TP + FN}$
$Precision = Confidence = \frac{TP}{TP + Fp}$
$F1 - score = \frac{2 * TP}{2 * TP + FP + FN}$

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

3. Results

The fundamental concept behind this work is to use MRI scans to classify two different forms of the brain disease Parkinson's: control and PD. Our suggested model was built on a convolutional neural network. The suggested model comprises five blocks for obtaining distinguishing information from MRI images and 1 block for identifying the most significant features of the 4 phases. We trained and evaluated our model to guarantee that the outcomes of the suggested technique are accurate, adequate, and efficient. Based on these findings, it was discovered that the suggested model produced improved outcomes when employing the MRI dataset with 97.9% accuracy. Latter, Table 4 below illustrates the equations that have been calculated which are: precision, recall, and F1-Score that have been evaluated for our approach using our constructed CNN architecture.

Table 3.	Evaluation	metries	results.
----------	------------	---------	----------

Class	Precision	Recall	F1 Score	Accuracy
Control (Healthy)	99	98	99	97.9
PD	98	92	88	97.9

There are many methods used to classify Parkinson's disease, each with its own characteristics, but in the end, all of them try to reach the highest accuracy. Thus, in this paper, we develop a new model that has a novel convolutional neural network structure applied to classify PD with superior precision. Our developed algorithm has three main advantages: 1The capacity to extract characteristics from images better than traditional methods 2) The possibility of achieving a classification with high accuracy compared to the method used by many other studies 3) The ability to diagnose time with a shorter time difference than the methods used, based on the structure used in the model's architecture, which led to achieving a high time difference.

There are many types of problems when compared with different datasets due to the gathering of datasets having several factors that affect the dataset, such as 1) the device used to collect the dataset; 2) the resolution of the image produced; and many additional aspects that play a critical role in the diagnosis of diseases. With all the challenges, our model achieved high-accuracy results compared to the other methods. As shown in Table 4, the model we developed clearly outperformed all prior research.

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

Ref.	Data Source	Subjects Number	Method	Acc
(Aich et al. 2019)	UCI	31;8HC + 23PD	SVM	97.57
(Al-Fatlawi, Jabardi, and Ling 2016)	UCI	31;8HC + 23PD	Deep Belief Network	94
(Al Sayaydeha and Mohammad 2019)	UCI	31;8HC + 23PD	Enhanced Fuzzy Min-Max Neural Network and OneR	94.21
(Ali, Khan, et al. 2019)	UCI	40; 20HC+20PD	SVM	70
(Ali, Zhu, et al. 2019)	UCI	40; 20HC+20PD	LDA	95
(Alqahtani et al. 2018)	UCI	31;8HC + 23 PD	AdaBoost	96.30
(Anand et al. 2018)	UCI	31;8HC + 23PD	KNN,	95.51
(Cai et al. 2018)	UCI	31;8HC + 23PD	Fuzzy-KNN	97.89
(Celik and Omurca 2019)	UCI	40;20HC+20PD	Logistic Regression	76.03
(Dinesh and He 2017)	UCI	31;8HC+23PD	Boosted Decision Tree	91.21
(Erdogdu Sakar, Serbes, and Sakar 2017)	UCI	50;8HC+42PD	SVM	96.43
(Gunduz 2019)	UCI	252;64HC+188 PD	CNN	869
(Islam et al. 2014)	UCI	31;8HC+23PD	SVM, Random Tree	97.37
(Senturk 2020)	UCI	31;8HC+23PD	SVM	93.84
(Khan, Mendes, and Chalup 2018)	UCI	31;8HC+23PD	Evolutionary Wavelet Neural Networks	92.9
(Kuresan, Samiappan, and Masunda 2019)	UCI	40;20HC+20PD	HMM	95.16
(Marar et al. 2018)	UCI	31;8HC+23PD	ANN	94.87
(Moharkan et al. 2017)	UCI	31;8HC+23PD	KNN	90
(Sheibani, Nikookar, and Alavi 2019)	UCI	31;8HC+23PD	Ensemble	90.6
(Yaman, Ertam, and Tuncer 2020)	UCI	80;40HC+40PD	SVM	91.25
(Montaña, Campos- Roca, and Pérez 2018)	Private	54;27HC+27PD	SVM	94.4
(Sztahó et al. 2017)	Private	88;33HC+55PD	SVM-RBF	89.3
(Wodzinski et al. 2019)	PC-GITA	50PD+50HC	ResNet	91.7
(Buongiorno et al. 2019)	Private	30;14HC+16PD	ANN	89.4
(Xiao et al. 2019)	Private	87PD; 53HC	CNN	89.0
(Yasaka et al. 2021)	Private	115HC+115PD	CNN	81.0
(Chakraborty, Aich, and Kim 2020)	PPMI	203HC +203PD	CNN	95.3

Table 4. The suggested architecture compares the same MRI dataset with various studies.

AURUM MÜHENDİSLİK SİSTEMLERİ VE MİMARLIK DERGİSİ

AURUM JOURNAL OF ENGINEERING SYSTEMS AND ARCHITECTURE

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

(Tremblay, Mei, and Frasnelli 2020)	Private	15HC+15PD	CNN	88.3
(Shinde et al. 2019)	Private	35 HC+45PD	CNN	80.0
(Piccardo et al. 2021)	Private	55HC+43PD	CNN	93.0
(Shen et al. 2018)	Private	225HC+125PD	Group Lasso Sparse Deep Belief Network	90.0
(Dai, Tang, and Wang 2019)	PPMI	127HC+214PD	CNN	84.2
(Magesh, Myloth, and Tom 2020)	PPMI	212HC+ 430PD	CNN	95.2
(Chien et al. 2020)	Private	145HC+234PD	CNN	86.0
(Hsu et al. 2020)	Private	6HC+196PD	CNN	85.0
(Ortiz et al. 2019)	PPMI	111HC+158PD	CNN	95.1
(Martinez-Murcia et al. 2018)	PPMI	194HC+448PD	CNN	94.1
(Oh et al. 2020)	Private	20HC+20PD	1D-CNN	88.3
(Zhang et al. 2020)	Public	2148HC+656P D	CNN	86.0
(Alharthi, Casson, and Ozanyan 2020)	Public	73 HC +93PD	CNN	95.5
(Butt et al. 2020)	Private	50 HC+64PD	LSTM	82.4
(Cantürk 2021)	N.A.	15HC +25PD	CNN	94.0
(Gil-Martín, Montero, and San-Segundo 2019)	N.A.	15HC+62PD	CNN	96.5
(Gazda, Hireš, and Drotár 2021)	N.A.	NA	CNN	94.7
(Pereira et al. 2018)	N.A.	18HC +74PC	CNN	95.0
(Ribeiro, Afonso, and Papa 2019)	N.A.	21HC+14PD	RNN	97.0
(Diaz et al. 2019)	PaHaW	38HC+37PD	CNN	86.67
(Diaz et al. 2021)	NewHand PD	NA	CNN-RNN	90.0
(Nõmm et al. 2020)	N.A.	17HC+17PD;	CNN	93
(Prince and De Vos 2018)	N.A.	866HC+949PD	CNN	62.1
OURs	Public	82HC+100PD	CNN	97.9

4. Conclusion

aurum

Certain systems inside healthcare may become crucial tools for clinicians to obtain an accurate classification for various diseases such as Parkinson's disease. Consequently, deep learning algorithms have recently been introduced to the medical profession and have proven to be effective for a variety of detection and prediction tasks. These applications have demonstrated that good collaboration between the

Cilt 7, Sayı 2 | Kış 2023 Volume 7, No 2 | Winter 2023

healthcare section and deep learning researchers can build a system for illness detection that is easier, simpler, and faster.

This article used public MRI images that were available on Kaggle as a dataset for the classification of two types of health subject conditions: control and Parkinson's disease (PD). Some techniques may require specific data properties, our work approach needed the dataset to be re-sized to 224x224 as a pre-processing phase before applying our developed CNN.

The top results evaluated by constructed CNN models had an accuracy of 97.9%. As a result, the deep learning system provided here can help clinicians diagnose Parkinson's disease more effectively. Finally, we contrasted our findings to other recent cutting-edge studies, and our proposed technique outscored them all.

REFERENCES

- Aich, Satyabrata, Hee-Cheol Kim, Kueh Lee Hui, Ahmed Abdulhakim Al-Absi, and Mangal Sain. 2019.
 "A supervised machine learning approach using different feature selection techniques on voice datasets for prediction of Parkinson's disease." In 2019 21st International Conference on Advanced Communication Technology (ICACT), 1116-21. IEEE.
- Al-azzawi, Athar Hussein A li, Saif Al-jumaili, Abdullahi Abdu Ibrahim, and Adil Deniz Duru. 2022.
 "Classification of epileptic seizure features from scalp electrical measurements using KNN and SVM based on Fourier Transform." In *AIP Conference Proceedings*, 020003. AIP Publishing LLC.
- Al-Fatlawi, Ali H, Mohammed H Jabardi, and Sai Ho Ling. 2016. "Efficient diagnosis system for Parkinson's disease using deep belief network." In 2016 IEEE Congress on evolutionary computation (CEC), 1324-30. IEEE.
- Al-Jumaili, Saif, Athar Al-Azzawi, Osman Nuri Uçan, and Adil Deniz Duru. 2023. 'Classification of the Level of Alzheimer's Disease Using Anatomical Magnetic Resonance Images Based on a Novel Deep Learning Structure.' in, *Diagnosis of Neurological Disorders Based on Deep Learning Techniques* (CRC Press).
- Al-Jumaili, Saif, Ahmed Al-Jumaili, Salam Alyassri, Adil Deniz Duru, and Osman Nuri Uçan. 2022.
 "Recent Advances on Convolutional Architectures in Medical Applications: Classical or Quantum?" In 2022 International Symposium on Multidisciplinary Studies and Innovative Technologies (ISMSIT), 800-05. IEEE.
- Al Sayaydeha, Osama Nayel, and Mohammad Falah Mohammad. 2019. "Diagnosis of the Parkinson disease using enhanced fuzzy min-max neural network and OneR attribute evaluation method." In 2019 International Conference on Advanced Science and Engineering (ICOASE), 64-69. IEEE.

- Alharthi, Abdullah S, Alexander J Casson, and Krikor B Ozanyan. 2020. 'Gait spatiotemporal signal analysis for Parkinson's disease detection and severity rating', *IEEE Sensors Journal*, 21: 1838-48.
- Ali, Hafsa Moontari, M Shamim Kaiser, and Mufti Mahmud. 2019. "Application of convolutional neural network in segmenting brain regions from MRI data." In *International conference on brain informatics*, 136-46. Springer.
- Ali, Liaqat, Shafqat Ullah Khan, Muhammad Arshad, Sardar Ali, and Muhammad Anwar. 2019. "A multimodel framework for evaluating type of speech samples having complementary information about Parkinson's disease." In 2019 International conference on electrical, communication, and computer engineering (ICECCE), 1-5. IEEE.
- Ali, Liaqat, Ce Zhu, Noorbakhsh Amiri Golilarz, Ashir Javeed, Mingyi Zhou, and Yipeng Liu. 2019.
 'Reliable Parkinson's disease detection by analyzing handwritten drawings: construction of an unbiased cascaded learning system based on feature selection and adaptive boosting model', *IEEE Access*, 7: 116480-89.
- Alqahtani, Ebtesam J, Fatimah H Alshamrani, Hajra F Syed, and Sunday O Olatunji. 2018. "Classification of Parkinson's disease using NNge classification algorithm." In 2018 21st Saudi Computer Society National Computer Conference (NCC), 1-7. IEEE.
- Anand, Anuj, Md Amaan Haque, John Sahaya Rani Alex, and Nithya Venkatesan. 2018. "Evaluation of Machine learning and Deep learning algorithms combined with dimentionality reduction techniques for classification of Parkinson's Disease." In 2018 IEEE international symposium on signal processing and information technology (ISSPIT), 342-47. IEEE.
- Buongiorno, Domenico, Ilaria Bortone, Giacomo Donato Cascarano, Gianpaolo Francesco Trotta, Antonio Brunetti, and Vitoantonio Bevilacqua. 2019. 'A low-cost vision system based on the analysis of motor features for recognition and severity rating of Parkinson's Disease', BMC Medical Informatics and Decision Making, 19: 1-13.
- Butt, Abdul Haleem, Filippo Cavallo, Carlo Maremmani, and Erika Rovini. 2020. "Biomechanical parameters assessment for the classification of Parkinson disease using bidirectional long shortterm memory." In 2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC), 5761-64. IEEE.
- Cai, Zhennao, Jianhua Gu, Caiyun Wen, Dong Zhao, Chunyu Huang, Hui Huang, Changfei Tong, Jun Li, and Huiling Chen. 2018. 'An intelligent Parkinson's disease diagnostic system based on a chaotic bacterial foraging optimization enhanced fuzzy KNN approach', *Computational and Mathematical Methods in Medicine*, 2018.
- Cantürk, Ismail. 2021. 'Fuzzy recurrence plot-based analysis of dynamic and static spiral tests of Parkinson's disease patients', *Neural Computing and Applications*, 33: 349-60.

- Celik, Enes, and Sevinc Ilhan Omurca. 2019. "Improving Parkinson's disease diagnosis with machine learning methods." In 2019 Scientific Meeting on Electrical-Electronics & Biomedical Engineering and Computer Science (EBBT), 1-4. Ieee.
- Chakraborty, Sabyasachi, Satyabrata Aich, and Hee-Cheol Kim. 2020. 'Detection of Parkinson's disease from 3T T1 weighted MRI scans using 3D convolutional neural network', *Diagnostics*, 10: 402.
- Chand, Ganesh B, Dominic B Dwyer, Guray Erus, Aristeidis Sotiras, Erdem Varol, Dhivya Srinivasan, Jimit Doshi, Raymond Pomponio, Alessandro Pigoni, and Paola Dazzan. 2020. 'Two distinct neuroanatomical subtypes of schizophrenia revealed using machine learning', *Brain*, 143: 1027-38.
- Chien, Chung-Yao, Szu-Wei Hsu, Tsung-Lin Lee, Pi-Shan Sung, and Chou-Ching Lin. 2020. 'Using artificial neural network to discriminate Parkinson's disease from other Parkinsonisms by focusing on putamen of dopamine transporter SPECT images', *Biomedicines*, 9: 12.
- Cigdem, Ozkan, and Hasan Demirel. 2018. 'Performance analysis of different classification algorithms using different feature selection methods on Parkinson's disease detection', *Journal of neuroscience methods*, 309: 81-90.
- Dai, Yin, Zheng Tang, and Yang Wang. 2019. 'Data driven intelligent diagnostics for Parkinson's disease', *IEEE Access*, 7: 106941-50.
- Danielyan, Arman, and Henry A Nasrallah. 2009. 'Neurological disorders in schizophrenia', *Psychiatric Clinics*, 32: 719-57.
- Diaz, Moises, Miguel Angel Ferrer, Donato Impedovo, Giuseppe Pirlo, and Gennaro Vessio. 2019.
 'Dynamically enhanced static handwriting representation for Parkinson's disease detection', *Pattern Recognition Letters*, 128: 204-10.
- Diaz, Moises, Momina Moetesum, Imran Siddiqi, and Gennaro Vessio. 2021. 'Sequence-based dynamic handwriting analysis for Parkinson's disease detection with one-dimensional convolutions and BiGRUs', *Expert Systems with Applications*, 168: 114405.
- Dinesh, Akshaya, and Jennifer He. 2017. "Using machine learning to diagnose Parkinson's disease from voice recordings." In 2017 IEEE MIT Undergraduate Research Technology Conference (URTC), 1-4. IEEE.
- Erdogdu Sakar, Betul, Gorkem Serbes, and C Okan Sakar. 2017. 'Analyzing the effectiveness of vocal features in early telediagnosis of Parkinson's disease', *Plos one*, 12: e0182428.
- Fontana, Roberto, Mario Agostini, Emanuele Murana, Mufti Mahmud, Elena Scremin, Maria Rubega, Giovanni Sparacino, Stefano Vassanelli, and Cristina Fasolato. 2017. 'Early hippocampal hyperexcitability in PS2APP mice: role of mutant PS2 and APP', *Neurobiology of aging*, 50: 64-76.

- Gazda, Matej, Máté Hireš, and Peter Drotár. 2021. 'Multiple-fine-tuned convolutional neural networks for Parkinson's disease diagnosis from offline handwriting', *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, 52: 78-89.
- Gil-Martín, Manuel, Juan Manuel Montero, and Rubén San-Segundo. 2019. 'Parkinson's disease detection from drawing movements using convolutional neural networks', *Electronics*, 8: 907.
- Gottapu, Ram Deepak, and Cihan H Dagli. 2018. 'Analysis of Parkinson's disease data', *Procedia computer science*, 140: 334-41.
- Gunduz, Hakan. 2019. 'Deep learning-based Parkinson's disease classification using vocal feature sets', *IEEE Access*, 7: 115540-51.
- Haq, Ejaz Ul, Huang Jianjun, Xu Huarong, Kang Li, and Lifen Weng. 2022. 'A hybrid approach based on deep cnn and machine learning classifiers for the tumor segmentation and classification in brain MRI', *Computational and Mathematical Methods in Medicine*, 2022.
- Hsu, Shih-Yen, Li-Ren Yeh, Tai-Been Chen, Wei-Chang Du, Yung-Hui Huang, Wen-Hung Twan, Ming-Chia Lin, Yun-Hsuan Hsu, Yi-Chen Wu, and Huei-Yung Chen. 2020. 'Classification of the multiple stages of Parkinson's Disease by a deep convolution neural network based on 99mTc-TRODAT-1 SPECT images', *Molecules*, 25: 4792.
- Huang, Lele, Dan Zhang, Jianling Ji, Yujie Wang, and Ruijun Zhang. 2021. 'Central retina changes in Parkinson's disease: a systematic review and meta-analysis', *Journal of neurology*: 1-9.
- Hughes, Andrew J, Susan E Daniel, Yoav Ben-Shlomo, and Andrew J Lees. 2002. 'The accuracy of diagnosis of parkinsonian syndromes in a specialist movement disorder service', *Brain*, 125: 861-70.
- Islam, Jyoti, and Yanqing Zhang. 2018. 'Brain MRI analysis for Alzheimer's disease diagnosis using an ensemble system of deep convolutional neural networks', *Brain informatics*, 5: 1-14.

——. 2020. 'GAN-based synthetic brain PET image generation', *Brain informatics*, 7: 1-12.

- Islam, Mohammad S, Imtiaz Parvez, Hai Deng, and Parijat Goswami. 2014. "Performance comparison of heterogeneous classifiers for detection of Parkinson's disease using voice disorder (dysphonia)." In 2014 International Conference on Informatics, Electronics & Vision (ICIEV), 1-7. IEEE.
- Kabir, Farjana. 2022. 'Alzheimer Parkinson Diseases 3 Class', Farjana Kabir, Accessed 20 octoper 2023. https://www.kaggle.com/datasets/farjanakabirsamanta/alzheimer-diseases-3-class/data.
- Khan, Maryam Mahsal, Alexandre Mendes, and Stephan K Chalup. 2018. 'Evolutionary Wavelet Neural Network ensembles for breast cancer and Parkinson's disease prediction', *Plos one*, 13: e0192192.
- Kollias, Dimitrios, Athanasios Tagaris, Andreas Stafylopatis, Stefanos Kollias, and Georgios Tagaris.
 2018. 'Deep neural architectures for prediction in healthcare', *Complex & Intelligent Systems*, 4: 119-31.

- Kumari, KH Vijaya, and Soubhagya Sankar Barpanda. 2023. 'Residual UNet with Dual Attention—An ensemble residual UNet with dual attention for multi-modal and multi-class brain MRI segmentation', *International Journal of Imaging Systems and Technology*, 33: 644-58.
- Kuresan, Harisudha, Dhanalakshmi Samiappan, and Sam Masunda. 2019. 'Fusion of WPT and MFCC feature extraction in Parkinson's disease diagnosis', *Technology and Health Care*, 27: 363-72.
- Lee, Sieh-Yang, Meng-Hsiang Chen, Pi-Ling Chiang, Hsiu-Ling Chen, Kun-Hsien Chou, Yueh-Cheng Chen, Chiun-Chieh Yu, Nai-Wen Tsai, Shau-Hsuan Li, and Cheng-Hsien Lu. 2018. 'Reduced gray matter volume and respiratory dysfunction in Parkinson's disease: a voxel-based morphometry study', *BMC neurology*, 18: 1-8.
- Lei, Baiying, Yujia Zhao, Zhongwei Huang, Xiaoke Hao, Feng Zhou, Ahmed Elazab, Jing Qin, and Haijun Lei. 2020. 'Adaptive sparse learning using multi-template for neurodegenerative disease diagnosis', *Medical Image Analysis*, 61: 101632.
- Leparulo, Alessandro, Mufti Mahmud, Elena Scremin, Tullio Pozzan, Stefano Vassanelli, and Cristina Fasolato. 2019. 'Dampened slow oscillation connectivity anticipates amyloid deposition in the PS2APP mouse model of Alzheimer's disease', *Cells*, 9: 54.
- Litjens, Geert, Thijs Kooi, Babak Ehteshami Bejnordi, Arnaud Arindra Adiyoso Setio, Francesco Ciompi, Mohsen Ghafoorian, Jeroen Awm Van Der Laak, Bram Van Ginneken, and Clara I Sánchez. 2017. 'A survey on deep learning in medical image analysis', *Medical Image Analysis*, 42: 60-88.
- Magesh, Pavan Rajkumar, Richard Delwin Myloth, and Rijo Jackson Tom. 2020. 'An explainable machine learning model for early detection of Parkinson's disease using LIME on DaTSCAN imagery', *Computers in biology and medicine*, 126: 104041.
- Mahmoudi, Tahereh, Zahra Mousavi Kouzahkanan, Amir Reza Radmard, Raheleh Kafieh, Aneseh Salehnia, Amir H Davarpanah, Hossein Arabalibeik, and Alireza Ahmadian. 2022. 'Segmentation of pancreatic ductal adenocarcinoma (PDAC) and surrounding vessels in CT images using deep convolutional neural networks and texture descriptors', *Scientific Reports*, 12: 3092.
- Mahmud, Mufti, M Shamim Kaiser, T Martin McGinnity, and Amir Hussain. 2021. 'Deep learning in mining biological data', *Cognitive computation*, 13: 1-33.
- Mahmud, Mufti, Mohammed Shamim Kaiser, Amir Hussain, and Stefano Vassanelli. 2018. 'Applications of deep learning and reinforcement learning to biological data', *IEEE transactions on neural networks and learning systems*, 29: 2063-79.
- Mahmud, Mufti, and Stefano Vassanelli. 2016. 'Processing and analysis of multichannel extracellular neuronal signals: state-of-the-art and challenges', *Frontiers in neuroscience*, 10: 248.
 - . 2019. 'Open-source tools for processing and analysis of in vitro extracellular neuronal signals', In Vitro Neuronal Networks: From Culturing Methods to Neuro-Technological Applications: 233-50.

- Marar, Shreerag, Debabrata Swain, Vivek Hiwarkar, Nikhil Motwani, and Akshar Awari. 2018. "Predicting the occurrence of Parkinson's Disease using various Classification Models." In 2018 International Conference on Advanced Computation and Telecommunication (ICACAT), 1-5. IEEE.
- Martinez-Murcia, Francisco J, Juan M Górriz, Javier Ramírez, and Andres Ortiz. 2018. 'Convolutional neural networks for neuroimaging in Parkinson's disease: Is preprocessing needed?', *International journal of neural systems*, 28: 1850035.
- Mathew, Nimmy Ann, RS Vivek, and PR Anurenjan. 2018. "Early diagnosis of Alzheimer's disease from MRI images using PNN." In 2018 international CET conference on control, communication, and computing (IC4), 161-64. IEEE.
- Miah, Yunus, Chowdhury Nazia Enam Prima, Sharmeen Jahan Seema, Mufti Mahmud, and M Shamim Kaiser. 2021. "Performance comparison of machine learning techniques in identifying dementia from open access clinical datasets." In Advances on Smart and Soft Computing: Proceedings of ICACIn 2020, 79-89. Springer.
- Moharkan, Zaid Ajaz, Harshul Garg, Tanupriya Chodhury, and Praveen Kumar. 2017. "A classification based Parkinson detection system." In 2017 International Conference On Smart Technologies For Smart Nation (SmartTechCon), 1509-13. IEEE.
- Montaña, David, Yolanda Campos-Roca, and Carlos J Pérez. 2018. 'A Diadochokinesis-based expert system considering articulatory features of plosive consonants for early detection of Parkinson's disease', *Computer Methods and Programs in Biomedicine*, 154: 89-97.
- Moujahid, Hicham, Bouchaib Cherradi, and Lhoussain Bahatti. 2020. "Convolutional neural networks for multimodal brain MRI images segmentation: A comparative study." In Smart Applications and Data Analysis: Third International Conference, SADASC 2020, Marrakesh, Morocco, June 25– 26, 2020, Proceedings 3, 329-38. Springer.
- Neromyliotis, Eleftherios, Theodosis Kalamatianos, Athanasios Paschalis, Spyridon Komaitis, Konstantinos N Fountas, Eftychia Z Kapsalaki, George Stranjalis, and Ioannis Tsougos. 2022.
 'Machine learning in meningioma MRI: past to present. A narrative review', *Journal of Magnetic Resonance Imaging*, 55: 48-60.
- Nõmm, Sven, Sergei Zarembo, Kadri Medijainen, Pille Taba, and Aaro Toomela. 2020. 'Deep CNN based classification of the archimedes spiral drawing tests to support diagnostics of the Parkinson's disease', *IFAC-PapersOnLine*, 53: 260-64.
- Noor, Manan Binth Taj, Nusrat Zerin Zenia, M Shamim Kaiser, Mufti Mahmud, and Shamim Al Mamun.
 2019. "Detecting neurodegenerative disease from MRI: a brief review on a deep learning perspective." In *Brain Informatics: 12th International Conference, BI 2019, Haikou, China, December 13–15, 2019, Proceedings 12*, 115-25. Springer.

- Norwitz, Nicholas G, David J Dearlove, Meng Lu, Kieran Clarke, Helen Dawes, and Michele T Hu. 2020. 'A ketone ester drink enhances endurance exercise performance in Parkinson's disease', *Frontiers in neuroscience*, 14: 584130.
- Oh, Shu Lih, Yuki Hagiwara, U Raghavendra, Rajamanickam Yuvaraj, N Arunkumar, M Murugappan, and U Rajendra Acharya. 2020. 'A deep learning approach for Parkinson's disease diagnosis from EEG signals', *Neural Computing and Applications*, 32: 10927-33.
- Ortiz, Andrés, Jorge Munilla, Manuel Martínez-Ibañez, Juan M Górriz, Javier Ramírez, and Diego Salas-Gonzalez. 2019. 'Parkinson's disease detection using isosurfaces-based features and convolutional neural networks', *Frontiers in neuroinformatics*, 13: 48.
- Pereira, Clayton R, Danilo R Pereira, Gustavo H Rosa, Victor HC Albuquerque, Silke AT Weber, Christian Hook, and João P Papa. 2018. 'Handwritten dynamics assessment through convolutional neural networks: An application to Parkinson's disease identification', *Artificial intelligence in medicine*, 87: 67-77.
- Piccardo, Arnoldo, Roberto Cappuccio, Gianluca Bottoni, Diego Cecchin, Luca Mazzella, Alessio Cirone, Sergio Righi, Martina Ugolini, Pietro Bianchi, and Pietro Bertolaccini. 2021. 'The role of the deep convolutional neural network as an aid to interpreting brain [18 F] DOPA PET/CT in the diagnosis of Parkinson's disease', *European radiology*, 31: 7003-11.
- Poldrack, Russell A, Krzysztof J Gorgolewski, and Gaël Varoquaux. 2019. 'Computational and informatic advances for reproducible data analysis in neuroimaging', *Annual Review of Biomedical Data Science*, 2: 119-38.
- Prince, John, and Maarten De Vos. 2018. "A deep learning framework for the remote detection of Parkinson's disease using smart-phone sensor data." In 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), 3144-47. IEEE.
- Ribeiro, Luiz CF, Luis CS Afonso, and Joao P Papa. 2019. 'Bag of samplings for computer-assisted Parkinson's disease diagnosis based on recurrent neural networks', *Computers in biology and medicine*, 115: 103477.
- Salvatore, Christian, Antonio Cerasa, Isabella Castiglioni, F Gallivanone, A Augimeri, M Lopez, G Arabia, M Morelli, MC Gilardi, and A Quattrone. 2014. 'Machine learning on brain MRI data for differential diagnosis of Parkinson's disease and Progressive Supranuclear Palsy', *Journal of neuroscience methods*, 222: 230-37.
- Senturk, Zehra Karapinar. 2020. 'Early diagnosis of Parkinson's disease using machine learning algorithms', *Medical Hypotheses*, 138: 109603.
- Shatte, Adrian BR, Delyse M Hutchinson, and Samantha J Teague. 2019. 'Machine learning in mental health: a scoping review of methods and applications', *Psychological medicine*, 49: 1426-48.

- Sheibani, Razieh, Elham Nikookar, and Seyed Enayatollah Alavi. 2019. 'An ensemble method for diagnosis of Parkinson's disease based on voice measurements', *Journal of medical signals and sensors*, 9: 221.
- Shen, Lu, Jun Shi, Bangming Gong, Yingchun Zhang, Yun Dong, Qi Zhang, and Hedi An. 2018. "Multiple empirical kernel mapping based broad learning system for classification of Parkinson's disease with transcranial sonography." In 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), 3132-35. IEEE.
- Shinde, Sumeet, Shweta Prasad, Yash Saboo, Rishabh Kaushick, Jitender Saini, Pramod Kumar Pal, and Madhura Ingalhalikar. 2019. 'Predictive markers for Parkinson's disease using deep neural nets on neuromelanin sensitive MRI', *NeuroImage: Clinical*, 22: 101748.
- Stoessl, A Jon, Stephane Lehericy, and Antonio P Strafella. 2014. 'Imaging insights into basal ganglia function, Parkinson's disease, and dystonia', *The Lancet*, 384: 532-44.
- Sztahó, Dávid, Miklós Gábriel Tulics, Klára Vicsi, and István Valálik. 2017. "Automatic estimation of severity of Parkinson's disease based on speech rhythm related features." In 2017 8th IEEE International Conference on Cognitive Infocommunications (CogInfoCom), 000011-16. IEEE.
- Thaha, M Mohammed, K Pradeep Mohan Kumar, BS Murugan, S Dhanasekeran, P Vijayakarthick, and A Senthil Selvi. 2019. 'Brain tumor segmentation using convolutional neural networks in MRI images', *Journal of medical systems*, 43: 1-10.
- Tolosa, Eduardo, Gregor Wenning, and Werner Poewe. 2006. 'The diagnosis of Parkinson's disease', *The Lancet Neurology*, 5: 75-86.
- Tremblay, Cécilia, Jie Mei, and Johannes Frasnelli. 2020. 'Olfactory bulb surroundings can help to distinguish Parkinson's disease from non-parkinsonian olfactory dysfunction', *NeuroImage: Clinical*, 28: 102457.
- Wodzinski, Marek, Andrzej Skalski, Daria Hemmerling, Juan Rafael Orozco-Arroyave, and Elmar Nöth.
 2019. "Deep learning approach to Parkinson's disease detection using voice recordings and convolutional neural network dedicated to image classification." In 2019 41st annual international conference of the IEEE engineering in medicine and biology society (EMBC), 717-20. IEEE.
- Xiao, Bin, Naying He, Qian Wang, Zenghui Cheng, Yining Jiao, E Mark Haacke, Fuhua Yan, and Feng Shi. 2019. 'Quantitative susceptibility mapping based hybrid feature extraction for diagnosis of Parkinson's disease', *NeuroImage: Clinical*, 24: 102070.
- Yaman, Orhan, Fatih Ertam, and Turker Tuncer. 2020. 'Automated Parkinson's disease recognition based on statistical pooling method using acoustic features', *Medical Hypotheses*, 135: 109483.
- Yamashita, Rikiya, Mizuho Nishio, Richard Kinh Gian Do, and Kaori Togashi. 2018. 'Convolutional neural networks: an overview and application in radiology', *Insights into imaging*, 9: 611-29.

- Yasaka, Koichiro, Koji Kamagata, Takashi Ogawa, Taku Hatano, Haruka Takeshige-Amano, Kotaro Ogaki, Christina Andica, Hiroyuki Akai, Akira Kunimatsu, and Wataru Uchida. 2021.
 'Parkinson's disease: Deep learning with a parameter-weighted structural connectome matrix for diagnosis and neural circuit disorder investigation', *Neuroradiology*: 1-12.
- Zhang, Hanrui, Kaiwen Deng, Hongyang Li, Roger L Albin, and Yuanfang Guan. 2020. 'Deep learning identifies digital biomarkers for self-reported Parkinson's disease', *Patterns*, 1.