## PAPER DETAILS

TITLE: ORGANIC DYES FOR TIO2 DYE-SENSITIZED SOLAR CELLS

AUTHORS: Mücella ÖZBAY KARAKUS, Tolga ÖNEN, Hidayet ÇETIN

PAGES: 28-28

ORIGINAL PDF URL: https://dergipark.org.tr/tr/download/article-file/303855

**Electronic Letters on Science & Engineering 12 (2) (2016)** 

## Special Issue BSW2016 Fifth Bozok Science Workshop: Nano Carbon Materials and Their Applications

Available online at www.e-lse.org

Bozok Science Workshop 2016, Yozgat, April 28-29, 2016.

## **ORGANIC DYES FOR TiO2 DYE-SENSITIZED SOLAR CELLS**

Mücella ÖZBAY KARAKUŞ<sup>1</sup>, Tolga ÖNEN<sup>2</sup>, Hidayet ÇETİN <sup>3\*</sup>

<sup>1</sup> Bozok University, Engineering and Architecture Faculty, Computer Engineering Department, Yozgat
<sup>2</sup> Bozok University, The Graduate School of Natural and Applied Sciences, Department of Physics, Yozgat
<sup>3\*</sup> Bozok University, Art and Science Faculty, Department of Physics, 66200, Yozgat.

**Abstract:** In this work, we extracted organic dyes from 13 different plants (purple pansy, linden, linden-sage mixture, pink begonia, cehirlik tulip, red beet, anchusa azurea, beet root, mullein, pink peony, red rose, henna, yellow marigold) and 7 fruits (black mulberry, red pepper, eggplant peel, red carrot, malta plum, ink-malta plum, blueberry). These dyes were used as sensitizer for nano-TiO<sub>2</sub> coated FTO dye-solar cell. 20 solar cells were prepared and electrical characteristics were obtained. Solar cells were fabricated as following procedure; TiO<sub>2</sub> paste which was on FTO layer was sintered at 450 °C for 30 min. After the sintering procedure, TiO<sub>2</sub> coated FTO layers were dipped prepared organic-based dyes for 24 h. Platinum coated FTO's were used as counter electrodes. The electrical characterizations of the fabricated solar cells were obtained under 1000 W/m<sup>2</sup> halogen lamp light. When short circuit current and fill factor values of the cells are compared, the black mulberry dye shows best results with the values of 2.263 A/m<sup>2</sup> current density and 0.498 fill factor.

Keywords: Natural Dyes; TiO<sub>2</sub> Nanostructure; Solar Cell.

## Acknowledgment:

This study has been supported by Bozok University Scientific Research Projects Department for 2015-FEF/A175 coded project.

\* Corresponding author; Tel.: +(90) 354 242 10 21 / 2595, E-mail: hidayet.cetin@bozok.edu.tr

ISSN 1305-8614 © 2016 www.e-lse.org All rights reserved.

LSE